













FLEX						
		M		SZT	KM	KG
5005	FLEX 3,0	3,00	-	24/16	110	1557
5000	FLEX 4,0 H	4,00	+	32/23	140	2334
5010	FLEX 5,0 H	5,00	+	40/28	180	2850
5015	FLEX 6,0 H	6,00	+	46/31	210	3100

OPTIONAL EQUIPMENT

-  SWEEPS 180 MM (set)
-  Transport LED lights

FLEX K						
		M		SZT	KM	KG
5030	Flex K 4,0H	4,00	+	32/23	180	3890
5035	Flex K 5,0H	5,00	+	40/28	240	4240
5040	Flex K 6,0H	6,00	+	46/31	280	4600

Preseeding cultivator FLEX



Preseeding cultivator FLEX

Pre-seeding cultivator FLEX is a well proven unit, designed for a seed bed preparation. Available in several working widths from 3 to 6m, as a carried unit (FLEX), or a trailed one (with transport chassis - FLEX-K). Machine consists of 6 independent working sections, which provide effective seed bed preparation. First section of adjustable track erradicators, is followed by the second one - 355 mm diameter string rollers. Behing, there is a section of 3-ranks of 32x10mm tines (straight or sweep sharepoints available) with independent working depth adjustment. Light adjustable leveling board is the fourth section of the machine, while two rollers following - the first one is a 300mm diameter string roller, with 400mm crosskill roller behind, make 5th and a 6th. All working sections have a swing mechanism, providing great field shape copying.



mandam.com.pl/en/cultivator-flex

Mandam Sp. z o.o.
Poland
44-100 Gliwice,
ul. Toruńska 14
0048 32 232 26 60
mandam.com.pl

[mandam.official](https://mandam.com.pl)



