

Chisel cultivator RHINO



The **RHINO CHISEL CULTIVATOR** is designed for stubble (up to 12 cm) and no-tillage cultivation (up to 35 cm depth). Available at working widths of 4.50 m and 6.00 m. The use of right- and left-side moldboards increases the intensity of stubble mixing, which reduces the intensity of phenolic compounds that negatively affect the development of cereals in the following year.

The use of the RHINO cultivator for deep no-till cultivation eliminates the need for ploughing, which reduces costs, eliminates the risk of an excessively compacted soil layer and increases the possibility of timely completion of treatments. The machine is equipped as standard with four rows of tines with double spring nonstop protection with an activation force of 650 kg per tine. Tine section is followed by cutting disc assembly. There are plenty of tillage rollers, tine screens, and a few accessory share points to choose from.

Each RHINO features: adjustable front support wheels for better working depth maintain, oversized 600/40/22'5 tires on a hydraulic adjustable chassis, and a braking system. The simultaneous machine height adjustment system is an option.



mandam.com.pl/en/rhino-en

Mandam Sp. z o.o.
44-100 Gliwice,
ul. Toruńska 14
0048 32 232 26 60
mandam.com.pl

[mandam.official](https://www.mandam.official)





#	RHINO						
		M		PC	PC	HP**	KG
6455	RHINO 4,5 H	4,50	+	15	10	340	6340
6450	RHINO 6,0 H	6,00	+	21	12	480	7380

** minimum power requirement for working at 10-12 cm depth

STANDARD EQUIPMENT:

- 4 rows of tines with double spring protection
- convenient stepless spring preload adjustment
- 550- 650 kg per tine protection
- maximum working depth of 30cm
- swingarm maintenance free IGUS™ bushings
- QL fine-grained steel used
- wearing parts from reputable suppliers
- 465mm notched discs on maintenance free hubs
- 85cm frame ground clearance
- hydraulic adjustment of working depth (HRGP)
- LED lights
- drag bar hitch
- pneumatic or hydraulic brake
- front support wheels

